





S3

The S3 creates stockpiles and minimizes loader traffic, labor and fuel costs while optimizing on-site safety. It is available in diesel-hydraulic and full electric version and can be plugged in, in any other e-version crusher or screen.



5	4	2	18
			
l/h	l/h	l/h	kWh
Diesel-hydraulic	Diesel-electric	Electric plug-in other machinery	Electric plug-in mains

Applications

- Stockpiling
- Transport
- Loading
- Sorting
- And others

- Tracked stacker without support legs
- Ability to stockpile, transport or load
- 75% cost saving capacity compared to loading shovel

METRIC



TECHNICAL SPECIFICATIONS		
Capacity up to		250 t
Weight		10,3 t
Feed size up to		200 mm
Inclinations		15°, 18°, 22°
Feeding chute		
Loading height		1519 - 2507 mm
	Loading width (back)	1680 mm
	Side loading length	2200 mm
Belt conveyor		•
Foldable main conveyor		•
Main conveyor belt (l x w)		18000 mm x 800 mm
Discharge height (min.-max.)		6660 mm, 7160 mm, 7780 mm
Main conveyor hydraulic foldable for transport		•
Swiveling range / adjustment of swiveling range		/
Height range of 4 legs (setting steps)		•
Track-unit: Length, total width, track shoe width		3000, 2290, 400 mm
speed track drive		1 km/h
Engine unit(s)		30 kW @ 1500 RPM - 38kW to 42kW @ 1800 RPM
Control		Control panel & wire remote
Available drive systems		
	Diesel/hydraulic drive	•
	e-drive Diesel/hybrid, electric plug-in & plug-out	•
	ZERO drive (no combustion engine, plug-in electric)	•

OPTIONS

Wear lining in HB450	•
Folding conveyor (S1e fits in container)	/
Increased feeding chute	width 2320 mm
Additional feeding station can be applied at any position	•
Radio remote	•
Scraper at drive drum	•
Working lights	•
Several chevron belts	/

TRANSPORT	
Transport l x w x h (mm)	11900 x 2290 x 2330 mm

LEGENDA	
•	applicable - available
/	not applicable- not available





METRIC



S3

The S3 creates stockpiles and minimizes loader traffic, labor and fuel costs while optimizing on-site safety. It is available in diesel-hydraulic and full electric version and can be plugged in, in any other e-version crusher or screen.



5	4	2	18
			
l/h	l/h	l/h	kWh
Diesel-hydraulic	Diesel-electric	Electric plug-in other machinery	Electric plug-in mains

Applications

Stockpiling
Transport
Loading
Sorting
And others

- Tracked stacker without support legs
- Ability to stockpile, transport or load
- 75% cost saving capacity compared to loading shovel



TECHNICAL SPECIFICATIONS	
Capacity up to	275 sT
Weight	11 sT
Feed size up to	7,8"
Inclinations	15°, 18°, 22°
Feeding chute	
Loading height	4'11" - 8'3"
	Loading width (back) 5'6"
	Side loading length 7'3"
Belt conveyor	•
Foldable main conveyor	•
Main conveyor belt (l x w)	59' x 2'7"
Discharge height (min.-max.)	21'10", 23'6", 25'6"
Main conveyor hydraulic foldable for transport	•
Swiveling range / adjustment of swiveling range	/
Height range of 4 legs (setting steps)	•
Track-unit: Length, total width, track shoe width	9'10", 7'6", 1'3"
speed track drive	0,6 mph
Engine unit(s)	30 kW @ 1500 RPM - 38kW to 42kW @ 1800 RPM
Control	Control panel & wire remote
Available drive systems	
	Diesel/hydraulic drive •
	e-drive Diesel/hybrid, electric plug-in & plug-out •
	ZERO drive (no combustion engine, plug-in electric) •

OPTIONS

Wear lining in HB450	•
Folding conveyor (S1e fits in container)	/
Increased feeding chute	width 7'7"
Additional feeding station can be applied at any position	•
Radio remote	•
Scraper at drive drum	•
Working lights	•
Several chevron belts	/

TRANSPORT	
Transport l x w x h	39'1 x 7'6" x 7'8"

LEGENDA	
	• applicable - available
	/ not applicable- not available

IMPERIAL

