

TFC 75

FEATURES & BENEFITS

The TFC 75 High Level Feeder Conveyor is a robust, high capacity hopper feeder that is suited to the most demanding of applications. Operators have the ability to directly discharge from wheel loaders/excavators eliminating the double handling of material onsite. The fully mobile TFC 75 allows a controlled feed of material into Ecotec shredders and screens.



Tier 3: Stage 3A CAT 4.4 - 4 cylinder diesel engine developing 83kW (111HP) @1800rpm
 Tier 4: Tier 4F / Stage IV - Caterpillar C4.4 - 4 cylinder diesel engine developing 82kW (110HP) @ 1800rpm
 Fuel tank volume: 325 litres

TRANSPORT DIMENSIONS	HIGH LEVEL FEEDER
Length	19.5m (63' 11")
Width	2.75m (9')
Height	3.12m (10' 2")
Weight (Est.)	25,000kg (55,115lbs)
Containerised shipping	40' x 9' 6" 2 x High Cube Containers

CONVEYOR DETAILS	HIGH LEVEL FEEDER
Conveyor length	22.6m (74' 2")
Belt width	1,200mm (47")
Discharge height	8m (26' 3") @ 18°
Max. discharge height	9.8m (32' 2") @ 24°
Production capacity	Up to 500TPH (551 US TPH)**

OPTIONS
Canvas dust covers on discharge conveyor
Canvas dust covers complete with dust hood on discharge conveyor
Twin drive discharge conveyor
Full length side skirting along discharge conveyor
High spec discharge conveyor head drum scraper
Anti-roll back flaps
Discharge belt upgraded to 3ply heavy duty belt
Discharge conveyor drive drum upgraded to ceramic lagging
Discharge conveyor underguard option length of mid section
Dust suppression at discharge conveyor head drum
Belt weigher option
Overband magnet at feedboot of discharge conveyor
Radio remote to start / stop feeder, raise / lower discharge
Pull cord E-stop running length of discharge conveyor
Radio remote to track machine
Feedboot lined 6mm wearplate
Twin drive feed conveyor
4" or 6" tipping grid fitted to feed conveyor

**Output potential dependent on feed material and settings. August 2018.