





The S5 creates stockpiles and minimizes loader traffic, labor and fuel costs while optimizing on-site safety. It is available in diesel-hydraulic and full electric version and can be plugged in, in any other e-version crusher or screen.



6	5	2	20
			
l/h	l/h	l/h	kWh
Diesel-hydraulic	Diesel-electric	Electric plug-in other machinery	Electric plug-in mains

Applications

Stockpiling
Transport
Loading
Sorting
And others

- Tracked stacker without support legs
- Ability to stockpile, transport or load
- 75% cost saving capacity compared to loading shovel

METRIC



Keestrack

TECHNICAL SPECIFICATIONS	
Capacity up to	300 t
Weight	12 t
Feed size up to	200 mm
Inclinations	9°, 16°, 22°
Feeding chute	
Loading height	1400 - 3050 mm
	Loading width (back) 1880 mm
	Side loading length 2200 mm
Belt conveyor	•
Foldable main conveyor	•
Main conveyor belt (l x w)	23000 mm x 1000 mm
Discharge height (min.-max.)	6050 mm, 8200 mm, 9350 mm
Main conveyor hydraulic foldable for transport	•
Swiveling range / adjustment of swiveling range	/
Height range of 4 legs (setting steps)	•
Track-unit: Length, total width, track shoe width	3000, 2290, 400 mm
speed track drive	1 km/h
Engine unit(s)	30 kW @ 1500 RPM - 38kW to 42kW @ 1800 RPM
Control	Control panel & wire remote
Available drive systems	
	Diesel/hydraulic drive •
	e-drive Diesel/hybrid, electric plug-in & plug-out •
	ZERO drive (no combustion engine, plug-in electric) •

OPTIONS

Wear lining in HB450	•
Folding conveyor (S1e fits in container)	/
Increased feeding chute	•
Additional feeding station can be applied at any position	•
Radio remote	•
Scraper at drive drum	•
Working lights	•
Several chevron belts	•

TRANSPORT	
Transport l x w x h (mm)	12000 x 2290 x 2760 mm





LEGENDA	
	• applicable - available
	/ not applicable- not available

METRIC



The S5 creates stockpiles and minimizes loader traffic, labor and fuel costs while optimizing on-site safety. It is available in diesel-hydraulic and full electric version and can be plugged in, in any other e-version crusher or screen.



6	5	2	20
 l/h	 l/h	 l/h	 kWh
Diesel-hydraulic	Diesel-electric	Electric plug-in other machinery	Electric plug-in mains

Applications

Stockpiling
Transport
Loading
Sorting
And others

- Tracked stacker without support legs
- Ability to stockpile, transport or load
- 75% cost saving capacity compared to loading shovel



TECHNICAL SPECIFICATIONS	
Capacity up to	330 sT
Weight	13 sT
Feed size up to	7,8"
Inclinations	9°, 16°, 22°
Feeding chute	
Loading height	4'7" - 10'
	Loading width (back) 6'2"
	Side loading length 7'3"
Belt conveyor	•
Foldable main conveyor	•
Main conveyor belt (l x w)	75'6" x 3'4"
Discharge height (min.-max.)	19'10", 26'10", 30'8"
Main conveyor hydraulic foldable for transport	•
Swiveling range / adjustment of swiveling range	/
Height range of 4 legs (setting steps)	•
Track-unit: Length, total width, track shoe width	9'10", 7'6", 1'3"
speed track drive	0,6 mph
Engine unit(s)	30 kW @ 1500 RPM - 38kW to 42kW @ 1800 RPM
Control	Control panel & wire remote
Available drive systems	
	Diesel/hydraulic drive •
	e-drive Diesel/hybrid, electric plug-in & plug-out •
	ZERO drive (no combustion engine, plug-in electric) •

OPTIONS

Wear lining in HB450	•
Folding conveyor (S1e fits in container)	/
Increased feeding chute	•
Additional feeding station can be applied at any position	•
Radio remote	•
Scraper at drive drum	•
Working lights	•
Several chevron belts	•

TRANSPORT	
Transport l x w x h	39'4" x 7'6" x 11'1"

LEGENDA	
	• applicable - available
	/ not applicable- not available

IMPERIAL

